

Part Number: 26599 Pro PAC™

These Pro PAC™ springs are designed for use in harsh, high-lift environments of .750" + drag race applications. They have the highest level of fatigue resistance available which is the key to extended life and durability.

Using the latest processing and manufacturing techniques the Pro PAC™ springs are crafted from the ultimate in high-tech super-clean chrome silicon alloy material. They are held to tighter stress relief and shot peen tolerances than any spring available in the market.

Description:	Dual Spring with Damper
O.D.:	1.625
I.D.:	0.769
Seat Load:	245 @ 2.050
Open Load:	706 @ 1.250
Coil Bind:	1.205
Rate (lbs./in.):	576
Titanium Retainer:	733, 784
Steel Retainer:	N/A
Cup/Seat:	4774, 4775
Shims:	4757



Pro PAC™ springs are packaged in individual spring enclosures, specially designed to prevent any rust formation as well prevention of any incidental spring-to-spring contact during shipping. This exclusive feature of the Pro PAC™ springs will prevent any scarring that could otherwise occur to the super high-tech surface of the Pro PAC™ springs.

Part Number: 26099

Created with new processing techniques, these springs have raised the bar on longevity and reliability. They are designed for use with a roller cam in a .750" + lift small block Super Gas and Fast Bracket drag race applications.

Description:	Dual Spring with Damper
O.D.:	1.625
I.D.:	0.769
Seat Load:	245 @ 2.050
Open Load:	706 @ 1.250
Coil Bind:	1.205
Rate (lbs./in.):	576
Titanium Retainer:	733, 784
Steel Retainer:	N/A
Cup/Seat:	4774, 4775
Shims:	4757

