

2.000	2.000	2.000	2.050	2.050	2.050	2.100	2.200	Installed Ht.
1.559	1.589/1.185	1.599	1.625	1.625	1.549	1.645	1.677	O.D.
.729	1.135/.731	.846	.769	.769	.719	.635	.635	I.D.
.750	.750	.700-.800	.750	.750	.750	.900	1.000	Max. Rec. Lift
490	293	491	576	576	549	686	728	Spring Rate
26075	26595	26091	26599	26099	26115	26082	26028	Part No.
Double	Single Beehive	Double	Double	Double	Double	Triple	Triple	# of Springs
Yes	No	No	Yes	Yes	Yes	No	No	Damper
								Spring Height (inches)
								2.300
							310	2.250
							346	2.200
						298	382	2.150
			216	216	203	332	419	2.100
183	135	255	245	245	230	366	455	2.050
207	150	270	274	274	257	401	492	2.000
232	165	295	303	303	285	435	528	1.950
256	179	319	331	331	312	469	564	1.900
281	194	344	360	360	340	504	601	1.850
305	209	368	389	389	367	538	637	1.800
330	223	393	418	418	395	572	674	1.750
354	238	417	447	447	422	606	710	1.700
379	253	442	475	475	450	641	746	1.650
403	267	466	504	504	477	675	783	1.600
428	282	491	533	533	505	709	819	1.550
452	297	516	562	562	532	744	856	1.500
477	311	540	591	591	559	778	892	1.450
501	326	565	619	619	587	812	928	1.400
526	340	589	648	648	614	847	965	1.350
550	355	614	677	677	642	881	1001	1.300
575	370	638	706	706	669	915	1038	1.250
599	384					949	1074	1.200
								1.150
								1.100
								1.050
								1.000
								.950
1.190	1.150	1.185	1.205	1.205	1.220	1.130	1.150	Coil Bind
721	785	781	733	733	732	739	739	Ti. Ret.
732			784	784		735, 722	735, 722	
N/A	N/A	N/A	N/A	N/A		N/A	N/A	Steel
4778	4711	4714	4774	4774	4700	4702	4709	Cup/Seat
4780			4775	4775	4781, 4782			
4757	4757	4757	4757	4757		4756	4756	Shims

Part #	Description
216	Superchart Professional Valvespring Reference Guide

