

Part Number: 26509 Pro PAC™

These Pro PAC™ springs are designed for use in harsh, high-lift environments of .750" + flat tappet cam applications. They have the highest level of fatigue resistance available which is the key to extended life and durability.

Using the latest processing and manufacturing techniques the Pro PAC™ springs are crafted from the ultimate in high-tech super-clean chrome silicon alloy material. They are held to tighter stress relief and shot peen tolerances than any spring available in the market.

Description:	Dual Spring with Damper
O.D.:	1.539
I.D.:	0.731
Seat Load:	197 @ 2.000
Open Load:	568 @ 1.250
Coil Bind:	1.135
Rate (lbs./in.):	494
Titanium Retainer:	732, 721
Steel Retainer:	N/A
Cup/Seat:	4700, 4772, 4773
Shims:	4757



Part Number: 26595 Pro PAC™

These Pro PAC™ springs are produced in a "beehive" form using ovate-wire and are designed for use in harsh, high-lift environments of 750+ flat tappet Winston Cup restrictor plate cam applications. They have the highest level of fatigue resistance available, which is the key to extended life and durability.

Using the latest processing and manufacturing techniques the Pro PAC™ springs are crafted from the ultimate in high-tech super-clean chrome silicon alloy material. They are held to tighter stress relief and shot peen tolerances than any spring available in the market.

Description:	Single Beehive Ovate
O.D.:	1.185/1.589
I.D.:	0.731/1.850
Seat Load:	150 @ 2.000
Open Load:	370 @ 1.250
Coil Bind:	1.110
Rate (lbs./in.):	293
Titanium Retainer:	785
Steel Retainer:	N/A
Cup/Seat:	4771
Shim:	4757



Pro PAC™ springs are packaged in individual spring enclosures, specially designed to prevent any rust formation as well prevention of any incidental spring-to-spring contact during shipping. This exclusive feature of the Pro PAC™ springs will prevent any scarring that could otherwise occur to the super high-tech surface of the Pro PAC™ springs.